

BarcoMed PCIe for Coronis

PCIe display controller for Coronis display systems



Product specifications**BARCOMED PCIE FOR CORONIS**

| General specifications | |
|------------------------|---|
| Bus | PCI Express X8, x16 |
| Dimensions | 106 x 176 x 16 mm (4.2 x 6.9 x 0.6") |
| Operating system | Windows 2000, XP 32/64, Vista XPDM |
| Platforms | Intel architectures |
| Graphics accelerator | Barco AURA |
| Memory | 128 MB |
| Look up table | 10 bit in / 10 bit out |
| Pixel depth | 10 bit |
| Electrical standard | Single link DVI complying to v1.0 |
| Video outputs | 2 DVI-D connectors |
| Supported resolutions | Up to 2560 x 2048 VGA at boot up |
| Approvals | FCC-B, CE, EN55022 B, EN 61000-6, IEC 60601-102 |
| Operating temperature | +10 to +60 °C (+50 to +140 °F) |
| Power consumption | < 15 W |

Last updated: 15 Mar 2023

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.